

UNCLASSIFIED

AD NUMBER

AD810792

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 31 MAR 1967.
Other requests shall be referred to Air Force Technical Applications Center, Washington, DC.

AUTHORITY

AFTAC ltr 28 Feb 1972

THIS PAGE IS UNCLASSIFIED

810792

NOISE ANALYSIS OF SINGLE CHANNEL DEGHOSTING FILTERS

31 March 1967

Prepared For

AIR FORCE TECHNICAL APPLICATIONS CENTER
Washington, D. C.

By

R. L. Sax
TELEDYNE, INC.

Under

Project VELA UNIFORM

Sponsored By

ADVANCED RESEARCH PROJECTS AGENCY
Nuclear Test Detection Office
ARPA Order No. 624

**BEST
AVAILABLE COPY**

NOISE ANALYSIS OF SINGLE CHANNEL DEGHOSTING FILTERS

SEISMIC DATA LABORATORY REPORT NO. 178

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date of Contract:	3 March 1967
Amount of Contract:	\$ 1,735,617
Contract Expiration Date:	2 March 1968
Project Manager:	William C. Dean (703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

Neither the Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which may have been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary.

TABLE OF CONTENTS

Page No.

ABSTRACT

I. INTRODUCTION	1
II. NOISE DATA	1
III. PERFORMANCE ANALYSIS PARAMETERS	2
IV. PRE-FILTERING AND DEGHOSTING MODELS	2
V. GAPPED FINITE DIFFERENCE FILTER	3
VI. RESULTS	5
VII. CONCLUSIONS	5

FIGURE

1. Noise Power Spectrum

TABLES

1. Data Unfiltered, Deghosting Method I.
2. Smoothed Second Difference Filter, Deghosting Method I.
3. Smoothed Fourth Difference Filter, Deghosting Method I.
4. Smoothed Second Difference Filter, Deghosting Method II.
5. Smoothed Fourth Difference Filter, Deghosting Method II.

ABSTRACT

Arrays of performance values showing the change in noise variance due to deghosting indicate significant sensitivity to both the deghosting method and pre-band pass filtering. As a specification for single channel deghosting, the apparent reflection coefficient used to derive the operator, should be constrained such that the noise amplification does not exceed a specified design criteria such as 1 db. Some typical results of such a test are given. The apparent reflection coefficient used to design the echo suppressor is observed as highly dependent on the echo time.

1. INTRODUCTION

Single channel deghosting is considered in the context of a modular approach to processing vertical array data for signal detection and measurement. The modules consist of:

- (1) pre-set band pass filter designed to improve detection probability of nearly vertical p-waves for a fixed false alarm probability (eg 0.02 or expectation of less than one false alarm per minute)
- (2) single channel deghosting operator for removal of echo distortion
- (3) possible multi-channel wave number-frequency filter, fan filter, for estimating the p-pulse and suppressing the ambient and signal-coda noise
- (4) in place of (3), possible use of signal correlation criteria for detecting and measuring the p-pulse.

Here, we are confined to evaluating the performance of single channel deghosting operators to determine the constraints required to prevent the deghosting operators from degrading the overall performance of the system.

2. NOISE DATA

The noise is obtained from a pseudo random number generating function, FORTRAN 63 RANF (-1). The algorithm has been tested and shown statistically to provide a sequence of random uncorrelated numbers. The sequence will not repeat until millions of samples have been called. The pseudo random numbers are averaged nine times to produce a nearly Gaussian input of uncorrelated samples. They are filtered twice in series using RECFIL3, a recursive narrow-band filter. The low frequency noise component is obtained with the frequency set at to .2 cps and $Q = f_0/\Delta f = 3.5$, and the high frequency to 2.0 cps, $Q = 6$. A plot of the power spectral density of a sample of the synthetic noise is shown in figure 1.

3. PERFORMANCE ANALYSIS PARAMETERS

The purpose of applying a single channel inverse deghosting operator is to suppress the echo reflected at the earth's surface. For teleseismic signals, the incidence angle is approximately 15° , thus the down-going pulse could be modeled with a reflection coefficient of 0.9 and the up-going pulse with a reflection coefficient of 1.1. In practice however, reflection coefficients greater than 1.0 lead to unstable operators, so that single channel echo-suppression is feasible only if we attempt to only partially remove the echo in isolating the up-going and down-going pulses. In analysing the performance of our echo-suppression filters, we try different reflection coefficients from zero to .9 at intervals of approximately .1; further we sample two-way echo times from .05 to 1.2 seconds at intervals of 0.5 seconds. Four minute noise samples are filtered. For each sample specified by the arrays of echo times and reflection coefficients, the variance of the noise is computed before and after applying the deghosting operator. The performance of the filter is gauged in decibels as $10 \log (\text{variance after filtering} / \text{variance before filtering})$. Negative values indicate a reduction in noise; positive an amplification in noise due to applying the deghosting filter.

4. PRE-FILTERING AND DEGHOSTING MODELS

This analysis will demonstrate that the performance on ambient noise is very sensitive to the bandpass filter and also on the numerical method used to deghost. Two different deghosting methods, two different bandpass filters, and unfiltered data make up a total of five cases to be evaluated by performance arrays. To produce each element in the array we operate on four minutes of data: each array, 16 hours of data, and for all five cases, 80 hours of data. The fact that all of these performances figures were computed with less than 40 minutes of computer time attests to speed of the bandpass

and deghosting operators.

The deghosting methods are described as method I and method II. Both are recursive filters which require only one multiplication per data point.

Method I.
$$Y_r = X_r + m/2 - R \cdot X_{r-m/2}$$

$$P_{mi+j} = R \cdot P_{m(i-1)+j} + Y_{mi+j}$$

$$M < M_1 < N$$

$$1 < j < M-1$$

X_r is the array of data containing the echo

R , reflection coefficient

P_r , deghosted data

m , echo-time measured in number of points

Method II.

$$Y_r = X_r + m/2 - 0.9 \cdot X_{r-m/2}$$

$$P_{mi+j} = R \cdot P_{m(i-1)+j} + Y_{mi+j}$$

The results evaluated for two band-pass filters employ gapped finite difference which involves only several subtractions per data point.

5. GAPPED FINITE DIFFERENCE FILTER

The gapped difference operator is given as $\{1, 0, 0, \dots, 0, -k\}$, where $k \leq 1$, and the gap is specified by the number of points between 1 and k . Here we are given by $k = 1$. The spectrum of the operator is given by

$$D(f) = i \sin\left(\frac{\pi f}{2 f_0}\right)$$

where the frequency of the first peak of the filter is related to the number of points in the gap, L .

$$L = \frac{S.R}{2 f_0}$$

$S. R.$, the sampling rate.

Note that series application of $D(f)$ can be used to generate higher differences

$$D^{(m)}(f_0) = (i^2)^{\frac{m}{2}} = (-1)^{\frac{m}{2}} = D^{2n}(f_0)$$

where $n = 1, 2, 3, \dots$ specifies the 2nd difference, 4th difference, etc. Taken as a filter we observe that for $n = \text{odd}$, the sign of the filter is reversed. The response of the filter is

$$D^{(2n)}(f) = (-1)^n \sin^{2n} \left(\frac{\pi f}{2 f_0} \right)$$

The gap, L , is determined by setting the first peak to the desired frequency. Nulls occur at integer multiples of twice the frequency of the first peak, and additional peaks occur at frequencies between the null's. Suppose at frequencies greater than the first null in the spectrum, for example at $f=2$, the signal and noise power are expected to attenuate rapidly with increasing frequency. These high frequency peaks will in this case produce negligible effects in the filtered output. If, however, we wish to insure attenuation of high frequency peaks in the noise spectrum we may apply in series with the filter a low pass smoothing operator $\{1, 0, 0, \dots, 0, +k\}$ where $k \leq 1$. The spectrum of the operator is given by $S(f)$.

$$S(f) = \cos \left(\frac{\pi f}{2 f_0} \right)$$

Repeated application of the smoothing operator leads to the operator

$$S^{(m)}(f) = \cos^m \left(\frac{\pi f}{2 f_0} \right)$$

where, for example, f_0 may be taken at the folding frequency.

For $k = 1$ there are no multiplications in either the smoothing or difference operator, so that the above digital operators are exceedingly fast. For $k = 1$ only an approximate inverse can be obtained. These are, in fact, simply deghosting operators. For $k \leq 1$, exact inverses can be obtained. The inverses can be designed as recursive filters with n multiplications per point where n is the number

of series applications of $D^{(n)}$ or $S^{(n)}$.

Smoothed gapped finite difference filters can be described spectrally as

$$F(f) = D^{(2n)}(f) S^{(m)}(f) \\ = (-1)^n \sin^{2n} \left(\frac{\pi f}{f_0} \right) \cos^m \left(\frac{\pi f}{2f_1} \right)$$

The two models evaluated were

1) Smoothed second difference filter

$$n = 1 \quad f_0 = 1.1 \text{ cps} \quad m = 4 \quad f_1 = 10 \text{ cps}$$

2) Smoothed fourth difference filter

$$n = 2 \quad f_0 = 1.1 \text{ cps} \quad m = 4 \quad f_1 = 10 \text{ cps}$$

6. RESULTS

Figure one shows the power spectrum of the noise data used in the evaluation of combined bandpass filters and deghosting operators. Table I through Table V, for different values of the reflection coefficient and the echo time (sum of up-hole and down-hole time), show the effect of the deghosting on the noise. Table I is for unfiltered data, on the other tables the noise is bandpass filtered. The performances figures in decibels show the effect of deghosting by comparing variance of the filtered noise after deghosting to the variance of filtered noise before deghosting. Examination of the performance figures show that both the bandpass filter and the deghosting method significantly affect the performance of single channel deghosting operators.

7. CONCLUSIONS

For unfiltered data and echo times between .2 sec and 0.35 seconds, and greater than 0.6 seconds the assumed reflection coefficient should not exceed 0.75 which is adequate for removal of 85% of the echo. For data prefiltered by smoothed second difference operators, the best performance is obtained with deghosting method I.

For echo times greater than 0.3 seconds, the reflection coefficient should not exceed 0.4 for removal of slightly less than half of the echo amplitude.

For data prefiltered by fourth difference operators, the best performance was obtained using deghosting method I. For echo times exceeding 0.3 seconds and less than 0.75 seconds, the reflection coefficient should not exceed 0.2 seconds. For echo times greater than 0.75 but less than 0.9 seconds, the reflection coefficient should not exceed 0.45; for echo times equal or greater than 0.9 seconds the reflection coefficient should not exceed 0.75. The fourth difference filter appears most suited as the bandpass filter. Due to deghosting, there will be little if any compromise of the expected 9 db gain obtained by applying the bandpass filter. Any residual echo distortion must be removed by multichannel filtering.

For display purposes, an adequate job of deghosting can be done on all channels in the absence of bandpass filtering. Provided that the assumed reflection coefficient does not exceed .75, less than 1 db total noise amplification is assured.




Figure 1. Noise Power Spectrum

PERFORMANCE OF DEGHOSTING FILTER IN DECIBELS
 $10 \log_{10}$ (VARIANCE AFTER DEGHOSTING/VARIANCE BEFORE DEGHOSTING)

Echo-Time (sec)	Reflection Coefficient -											
	0	.09	.18	.27	.36	.45	.54	.63	.72	.81	.90	
.05	0	-0.8	-1.5	-2.3	-3.1	-3.9	-4.7	-5.5	-6.3	-7.0	-7.6	
.10	-0.0	-0.7	-1.3	-2.0	-2.6	-3.2	-3.7	-4.3	-4.8	-5.2	-5.6	
.15	-0.0	-0.6	-1.1	-1.6	-2.1	-2.6	-3.0	-3.4	-3.7	-4.1	-4.2	
.20	-0.0	-0.5	-0.9	-1.2	-1.5	-1.7	-1.9	-1.9	-1.9	-1.6	-1.4	
.25	-0.3	-0.4	-0.7	-0.9	-0.9	-0.8	-0.4	.3	1.4	3.2	6.3	
.30	-0.0	-0.4	-0.7	-0.9	-0.9	-0.8	-0.5	-0.0	.0	2.1	4.6	
.35	-0.0	-0.4	-0.8	-1.0	-1.2	-1.3	-1.3	-1.2	-0.9	-0.3	1.0	
.40	-0.0	-0.4	-0.8	-1.2	-1.5	-1.7	-1.6	-1.6	-1.6	-0.9	1.0	
.45	-0.0	-0.5	-0.9	-1.3	-1.6	-1.6	-2.0	-2.1	-2.0	-1.7	-0.8	
.50	-0.0	-0.5	-0.9	-1.3	-1.6	-1.9	-2.0	-2.1	-2.0	-1.5	-0.3	
.55	-0.0	-0.5	-0.8	-1.2	-1.5	-1.7	-1.9	-1.9	-1.7	-1.2	.1	
.60	-0.0	-0.4	-0.8	-1.1	-1.3	-1.5	-1.6	-1.6	-1.3	-0.7	1.0	
.65	-0.0	-0.3	-0.6	-0.9	-1.1	-1.2	-1.3	-1.2	-0.9	-0.1	1.7	
.70	-0.0	-0.3	-0.5	-0.6	-0.7	-0.7	-0.7	-0.5	-0.1	.7	2.2	
.75	-0.0	-0.2	-0.3	-0.4	-0.4	-0.3	-0.0	.4	1.1	2.3	4.6	
.80	-0.0	-0.1	-0.2	-0.3	-0.2	-0.1	.2	.6	1.3	2.5	4.6	
.85	-0.0	-0.1	-0.2	-0.2	-0.2	-0.1	.1	.5	1.2	2.3	4.7	
.90	-0.0	-0.1	-0.2	-0.3	-0.3	-0.2	-0.0	.3	.9	1.9	4.2	
.95	-0.0	-0.1	-0.2	-0.3	-0.3	-0.3	-0.2	.1	.5	1.3	3.1	
1.00	-0.0	-0.1	-0.2	-0.3	.3	-0.3	-0.2	.0	.4	1.2	2.8	
1.05	-0.0	-0.1	-0.2	-0.2	-0.2	-0.2	-0.1	.1	.5	1.1	2.7	
1.10	-0.0	-0.1	-0.1	-0.1	-0.1	-0.0	.1	.3	.7	1.5	3.1	
1.15	-0.0	-0.0	.0	.0	.1	.2	.4	.7	1.2	2.2	4.4	
1.20	-0.0	.0	.1	.2	.3	.5	.7	1.1	1.7	2.7	4.5	

Table 1. Data Unfiltered, Deghosting Method I.

PERFORMANCE OF DEHOSTING FILTER IN DECIBELS
 $10 \log_{10}(\text{VARIANCE AFTER DEHOSTING/VARIANCE BEFORE DEHOSTING})$

	Reflection Coefficient -									
	.0	.09	.14	.27	.45	.54	.63	.72	.81	.90
.25										
.30										
.35										
.40										
.45										
.50										
.55										
.60										
.65										
.70										
.75										
.80										
.85										
.90										
.95										
1.00										
1.05										
1.10										
1.15										
1.20										

Table 2. Smoothed Second Difference Filter, Deghosting Method I.

PERFORMANCE OF DEGHOSTING FILTER IN DECIBELS
 $10 \log_{10}$ (VARIANCE AFTER DEGHOSTING/VARIANCE BEFORE DEGHOSTING)

	Reflection Coefficient -										Echo-Time (sec)
	0	.09	.18	.27	.36	.45	.54	.63	.72	.81	.90
.05	0	-0.8	-1.5	-2.3	-3.1	-3.9	-4.6	-5.4	-6.2	-6.8	-7.3
.10	0	-0.6	-1.3	-1.9	-2.5	-3.1	-3.7	-4.1	-4.5	-4.9	-5.2
.15	0	-0.5	-1.0	-1.5	-2.0	-2.4	-2.9	-3.3	-3.6	-3.9	-4.1
.20	0	-0.3	-0.7	-1.1	-1.4	-1.8	-2.1	-2.4	-2.7	-2.9	-3.2
.25	0	-0.1	-0.3	-0.5	-0.7	-0.9	-1.2	-1.4	-1.7	-1.9	-2.2
.30	0	.1	.1	.1	.1	.1	.0	-.1	-.2	-.4	-.5
.35	0	.3	.5	.6	1.0	1.2	1.4	1.7	1.9	2.3	2.6
.40	0	.4	.9	1.3	1.8	2.3	2.9	3.5	4.4	5.0	5.3
.45	0	.6	1.2	1.8	2.4	3.1	3.9	4.8	5.9	7.3	9.3
.50	0	.6	1.3	2.0	2.8	3.7	4.6	5.8	7.1	9.3	11.8
.55	0	.7	1.4	2.1	2.9	3.8	4.9	6.0	7.5	9.3	12.1
.60	0	.6	1.3	2.0	2.8	3.7	4.7	5.9	7.4	9.3	12.4
.65	0	.6	1.1	1.8	2.5	3.3	4.2	5.4	6.8	8.0	11.9
.70	.6	.4	.9	1.5	2.0	2.7	3.5	4.4	5.6	7.1	9.2
.75	0	.3	.7	1.1	1.5	2.0	2.6	3.4	4.3	5.7	8.2
.80	0	.2	.4	.6	.9	1.3	1.8	2.4	3.2	4.4	6.7
.85	0	.0	.1	.2	.4	.6	1.0	1.4	2.1	3.2	5.3
.90	0	-.1	-.1	-.1	-.1	.0	.2	.6	1.2	2.3	4.6
.95	0	-.2	-.3	-.4	-.5	.5	-.4	-.2	.3	1.2	3.8
1.00	0	-.2	-.5	-.7	-.8	.9	-.9	-.6	-.5	.1	1.4
1.05	0	-.3	-.5	-.8	-.9	-.3	-.1	-.1	-.9	-.5	.6
1.10	0	-.3	-.5	-.8	-.9	-.1	-.1	-.1	-.7	-.2	1.8
1.15	0	-.3	-.5	-.7	-.8	.0	-.7	-.5	-.1	.7	2.4
1.20	0	-.2	-.4	-.5	-.6	.5	-.3	.1	.9	2.1	4.6

Table 3. Smoothed Fourth Difference Filter, Deghosting Method I.

PERFORMANCE OF DEGHOSTING FILTER IN DECIBELS

10 LOG 10 (VARIANCE AFTER DEGHOSTING/VARIANCE BEFORE DEGHOSTING)

Echo Time (sec)	Reflection Coefficient -									
	.8	.09	.16	.27	.36	.45	.54	.63	.72	.81
.05	-11.7	-11.7	-11.6	-11.4	-11.2	-10.9	-10.5	-10.0	-9.3	-8.5
.10	-6.4	-6.4	-6.3	-6.2	-6.2	-6.0	-5.9	-5.8	-5.7	-5.6
.15	-3.2	-3.2	-3.2	-3.3	-3.4	-3.5	-3.6	-3.8	-4.0	-4.2
.20	-1.0	-1.0	-1.1	-1.3	-1.5	-1.8	-2.1	-2.4	-2.7	-3.1
.25	.6	.5	.4	.2	.0	.3	.6	-1.0	-1.3	-1.8
.30	1.7	1.7	1.6	1.4	1.3	1.1	.9	.7	.7	.8
.35	2.5	2.5	2.4	2.4	2.5	2.2	2.2	2.3	2.6	3.1
.40	3.1	3.1	3.1	3.0	3.0	2.8	2.7	2.8	3.0	3.5
.45	3.5	3.5	3.5	3.5	3.5	3.3	3.2	3.3	3.5	4.0
.50	3.7	3.7	3.7	3.8	3.8	3.6	3.5	3.6	3.8	4.3
.55	3.8	3.8	3.8	3.9	3.9	3.7	3.6	3.7	3.9	4.4
.60	3.8	3.8	3.8	3.9	3.9	3.7	3.6	3.7	3.9	4.4
.65	3.8	3.8	3.8	3.9	3.9	3.7	3.6	3.7	3.9	4.4
.70	3.6	3.6	3.7	3.7	3.8	3.6	3.5	3.6	3.8	4.3
.75	3.5	3.5	3.5	3.5	3.6	3.4	3.3	3.4	3.6	4.1
.80	3.4	3.4	3.4	3.4	3.5	3.3	3.2	3.3	3.5	4.0
.85	3.2	3.2	3.2	3.2	3.3	3.1	3.0	3.1	3.3	3.8
.90	3.1	3.1	3.1	3.1	3.2	3.0	2.9	3.0	3.2	3.6
.95	3.0	3.0	3.0	3.0	3.1	2.9	2.8	2.9	3.1	3.4
1.00	3.0	2.9	2.9	2.9	3.0	2.8	2.7	2.8	3.0	3.3
1.05	2.9	2.9	2.9	2.9	3.0	2.8	2.7	2.8	3.0	3.3
1.10	2.8	2.8	2.8	2.8	2.9	2.7	2.6	2.7	2.9	3.2
1.15	2.8	2.8	2.8	2.8	2.9	2.7	2.6	2.7	2.9	3.2
1.20	2.8	2.8	2.8	2.8	2.9	2.7	2.6	2.7	2.9	3.2

Table 4. Smoothed Second Difference Filter, Deghosting, Method II.

PERFORMANCE OF DEGHOSTING FILTER IN DECIBELS
 $10 \log_{10}$ (VARIANCE AFTER DEGHOSTING/VARIANCE BEFORE DEGHOSTING)

	Reflection Coefficient --											
	.0	.09	.18	.27	.36	.45	.54	.63	.72	.81	.90	
.05	-16.8	-10.7	-10.7	-10.5	-10.5	-10.0	-9.5	-9.0	-8.4	-7.8	-7.3	
.10	-5.3	-5.3	-5.2	-5.1	-5.0	-4.9	-4.8	-4.8	-4.8	-4.9	-5.2	
.15	-2.0	-2.0	-2.1	-2.1	-2.0	-2.4	-2.6	-2.9	-3.2	-3.7	-4.1	
.20	.2	.2	.0	-.1	-.4	-.8	-1.2	-1.6	-2.1	-2.6	-3.2	
.25	1.6	1.8	1.6	1.4	1.0	.6	.1	-.4	-1.0	-1.6	-2.2	
.30	3.0	3.0	2.8	2.6	2.3	1.9	1.5	1.0	.5	.0	-.5	
.35	3.9	3.8	3.6	3.6	3.5	3.3	3.1	2.9	2.8	2.7	2.8	
.40	4.5	4.5	4.5	4.5	4.5	4.5	4.6	4.8	5.3	6.2	8.3	
.45	4.9	4.9	5.0	5.1	5.2	5.4	5.7	6.1	6.8	7.7	9.3	
.50	5.1	5.1	5.2	5.4	5.6	6.0	6.4	7.1	8.0	9.4	11.8	
.55	5.2	5.2	5.3	5.5	5.8	6.1	6.7	7.4	8.3	9.8	12.1	
.60	5.0	5.1	5.2	5.4	5.6	6.0	6.5	7.2	8.2	9.8	12.4	
.65	4.6	4.8	4.9	5.0	5.2	5.6	6.0	6.7	7.6	9.2	11.9	
.70	4.4	4.4	4.5	4.6	4.7	4.9	5.2	5.7	6.4	7.5	9.2	
.75	3.9	3.9	3.9	3.9	4.0	4.1	4.3	4.6	5.1	6.1	8.2	
.80	3.3	3.3	3.2	3.2	3.2	3.2	3.3	3.5	4.0	4.8	6.7	
.85	2.6	2.5	2.5	2.5	2.4	2.4	2.4	2.5	2.9	3.6	5.3	
.90	1.8	1.8	1.8	1.7	1.6	1.5	1.5	1.6	1.9	2.6	4.6	
.95	1.1	1.1	1.0	.9	.8	.7	.6	.7	.9	1.5	3.0	
1.00	.6	.5	.5	.3	.2	.1	-.0	-.1	-.0	.4	1.5	
1.05	.2	.2	.1	-.0	-.1	-.3	-.4	-.5	-.5	-.3	.6	
1.10	.1	.1	.0	-.1	-.2	-.5	-.4	-.4	-.3	.0	1.0	
1.15	.2	.2	.2	.1	.1	.1	.1	.2	.4	1.0	2.4	
1.20	.6	.5	.5	.5	.5	.5	.6	.9	1.4	2.4	4.5	

Table 5. Smoothed Fourth Difference Filter, Deghosting Method II.

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
TELEDYNE, INC. ALEXANDRIA, VIRGINIA 22314		Unclassified	
		2b. GROUP -----	
3. REPORT TITLE			
NOISE ANALYSIS OF SINGLE CHANNEL DEGHOSTING FILTERS			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
Scientific Report			
5. AUTHOR(S) (Last name, first name, initial)			
Sax, R. L.			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
31 March 1967		13	0
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)	
F 33657-67-C-1313		SDL Report No. 178	
a. PROJECT NO. VELA T/6702		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c. ARPA Order No. 624		-----	
d. ARPA Program Code No. 5810			
10. AVAILABILITY/LIMITATION NOTICES			
This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Chief, AFTAC.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
-----		Advanced Research Projects Agency Nuclear Test Detection Office Washington, D. C.	
13. ABSTRACT			
<p>Arrays of performance values showing the change in additive noise variance due to single channel deghosting indicate significant sensitivity to both the deghosting method and band pass filtering. Only part of the echo can be removed feasibly, for example, with less than one db increase in the noise, by the single channel deghosting filter. The maximum fraction of the echo which can be removed varies greatly with the echo time, especially if the noise was band pass filtered.</p>			

Deghosting

Pre-band pass filtering

Synthetic noise

Echo-suppression filters

[illegible]

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S).** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES Enter the total number of references cited in the report.

10. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

5b, 5c, & 5d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

CTIONS imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall and with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.